

## SAFETY DATA SHEET

### 1 IDENTIFICATION

Product name :JP-F63  
 Name of company :Hitachi Industrial Equipment Systems Co., Ltd  
 Address :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan  
 Tel :+81-294-36-8682  
 Fax :+81-294-36-8975  
 Recommended use of the chemical and restrictions on use :Printing Ink for industrial Marking

### 2 HAZARDS IDENTIFICATION

Physico-chemical endpoints : Flammable liquid Category 2  
 Acute toxicity - oral : Category 5  
 Acute toxicity - dermal : Not available  
 Acute toxicity - inhalation (air) : Not identified  
 Acute toxicity - inhalation (vapors) : Category 5  
 Acute toxicity - inhalation (dust, mist) : Not available  
 Skin corrosion/irritation : Category 2  
 Eye damage/irritation : Category 2  
 Sensitization - respiratory : Not identified  
 Sensitization - skin : Not identified  
 Germ cell mutagenicity : Category 1  
 Carcinogenicity : Not identified  
 Toxic to reproduction : Category 1  
 Effects on or via lactation : Not identified  
 Specific target organ systemic toxicity : (Single exposure)  
     Category 1 Sensory system  
     Category 1 Systemic toxicity  
     Category 1 Central nervous system  
     Category 2 Kidney  
     Category 3 Respiratory tract irritation  
 :(Repeated exposure)  
     Category 1 Liver  
     Category 1 Sensory system  
     Category 1 Central nervous system  
     Category 1 Peripheral nervous system  
     Category 2 Nervous system  
 Aspiration toxicity : Category 2  
 Hazardous to the aquatic environment  
 -Acute hazard : Not available  
 -Chronic hazard : Not available

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**GHS label elements**

Hazard symbols:

**Signal word:** Danger**Hazard statement and precautionary statement:**

- Highly flammable liquid and vapor
- May be harmful if swallowed
- May be harmful if inhaled
- Causes skin irritation
- Causes serious eye irritation
- May cause genetic defects
- May damage fertility or the unborn child
- Causes damage to Sensory system, systemic toxicity or central nervous system-single exposure
- May cause damage to kidney-single exposure
- May cause damage to airway irritant-single exposure
- Causes damage to liver, sensory system, central nervous system or peripheral nervous system through prolonged or repeated exposure.
- May cause damage to nervous system through prolonged or repeated exposure
- May be harmful if swallowed and enters airways

**Precautionary statements:**

- Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

**Prevention:**

- Keep away from ignition sources such as heat/sparks/open flame– No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

**Response:**

- In case of fire, use dry chemical, CO<sub>2</sub>, water splay (fog) or foam for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

- Collect spillage.

**Storage:**

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

**Disposal:**

- Waste must be disposed of according to applicable regulations.

### 3 Composition/information on ingredients

**Substance or mixture;** mixture

**Composition:**

Chemical name	concentration (%)	CAS number
2-butanone	50-60	78-93-3
Ethanol	1-10	64-17-5
Methanol	1-10	67-56-1
2-Propanol	0.1-1	67-63-0

### 4 First-aid measures

**Inhalation;**

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

**Skin contact;**

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

**Eye contact;**

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible. and refer for medical attention.

**Ingestion;**

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medical attention.

### 5 Fire-fighting measures

**Suitable extinguishing media;**

Use dry chemical, CO<sub>2</sub>, water splay (fog) or foam.

**Fire fighting procedures;**

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Unusual fire/explosion hazard;**

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

**Special protective equipment and precautions for fire fighters;**

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

**6 Accidental release measures**

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

**7 Handling and storage****Handling;**

Use only in the well-ventilated areas.

Make available in the work area emergency shower and eyes wash.

Avoid contact with skin or eyes.

**Storage;**

Close up the container and keep it in dark cool(0~20°C) place.

Keep away from combustible materials and sources of ignition.

**8 Exposure controls/personal protection****Exposure guidelines:**

ACGIH TLV-TWA (ppm)

2-butanone	:200
Ethanol	:1000
Methanol	:200(skin)
2-Propanol	:200

ACGIH STEL(ppm)

2-butanone	:300
Ethanol	:No data
Methanol	:250(skin)
2-Propanol	:400

**9 Physical and chemical properties**

Appearance	
Physical state	:Liquid
Color	:Clear
Odor	:Solvent odor
Boiling point <sup>2)</sup>	:80-150°C
Flash point	:-4.0°C (closed cup)
Upper/lower flammability or explosive limits <sup>2)</sup>	:Lower 1.7 vol%、Upper 11.4 vol%
Vapor pressure <sup>2)</sup>	:9.5kPa (20°C)
Vapor density (Air=1) <sup>2)</sup>	:2.41 (2-butanone)
Relative density	:0.86(20°C)
Solubility (Water) <sup>2)</sup>	:29g/100mL (20°C)(2-butanone)

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Partition coefficient: n-octanol/water <sup>2)</sup>	:0.29 (2-butanone)
Auto-ignition temperature <sup>2)</sup>	:404°C
Decomposition temperature	:No data

## 10 Stability and reactivity

Stability: The product is stable.

Conditions and materials to avoid: Not available

Hazardous decomposition products: These products are carbon oxides

## 11 Toxicological information

### Acute toxicity:

#### 2-butanone

LD50(oral,rat): 2737mg/kg(TXAPA9 19, 699, 1971)

LCLo(ihl,rat): 23500mg/m<sup>3</sup>/8h(AIHAAP 20, 364, 1959)

LD50(skin,rabbit): 6480mg/kg(SHELL\* MSDS-5390-4)

TCLo(ihl,human): 1000mg/m<sup>3</sup>(VCVGK\* -, 417, 1994)

LDLo(oral,human): 714.3mg/kg(VCVGK\* -, 417, 1994)

#### Ethanol

TDLo(oral,man): 700mg/kg(NTOTDY 8,77,1986)

LD50(oral,rat): 9000mg/kg(VCVGK\* -, 93, 1984)

LC50(ihl,rat): 20000ppm/10h(NPIRI\* 1,44,1974)

TCLo(ihl,human): 2500mg/m<sup>3</sup>/20M(VCVGK\* -, 93,1984)

#### Methanol

LD50(oral,rat): 5628mg/kg(GTPZAB 19(11),27,1975)

LC50(ihl,rat): 64000ppm/4h(NPIRI\* 1,74,1974)

TDLo(oral,man): 9450µL/kg(AJEMEN 16,538,1998)

TCLo(ihl,human): 300ppm(NPIRI\* 1,74,1974)

#### 2-Propanol

LD50(oral,rat): 5000mg/kg(VCVGK\* -, 97, 1984)

LC50(ihl,rat): 72600mg/m<sup>3</sup>(VCVGK\* -, 97, 1984)

LC50(ihl,mouse): 53000mg/m<sup>3</sup>(VCVGK\* -, 97, 1984)

TDLo(oral,human): 286mg/kg(VCVGK\* -, 97, 1984)

### Skin corrosion/irritation:

#### 2-butanone

Skin; rabbit; 402mg/24h; Mild(TXAPA9 19, 276, 1971)

#### Ethanol

Skin; rabbit; 20mg/24h; Moderate(85JCAE -, 189, 1986)

#### Methanol

Skin; rabbit; 20mg/24h; Moderate(85JCAE -,187,1986)

#### 2-Propanol

Skin; rabbit; 500mg; Mild(NTIS\*\* AD-A106-944)

### Serious eye damage/irritation:

#### 2-butanone

Eye; rabbit; 80mg(TXAPA9 19, 276, 1971)

#### Ethanol

rabbit; 100mg/4S; Moderate(FCTOD7 20,573,1982)

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Methanol**

Eye; rabbit; 100mg/24h; Moderate(85JCAE -,187,1986)

**2-Propanol**

Eye; rabbit; 100mg/24h; Moderate(85JCAE -,191,1986)

**Respiratory or skin sensitization:****2-butanone**

Not available

**Ethanol**

Not available

**Methanol**

Allergic dermatitis; human, skin(PATTY 4th,1994)

No skin sensitization ;Magnusson-Kligman maximization test, guinea pig(EHC 196,1997: DFGOT vol. 16,2001)

**2-Propanol**

Not available

**Germ cell mutagenicity:****2-butanone**

Reverse mutation assay in *S.typhimuriun* and *E.coli*; Negative

Sex chromosome loss and nondisjunction; *S.cerevisiae*; 33800ppm(MUREAV 149, 339, 1985)

**Ethanol**

DNA damage; *S.cerevisiae*; 850mmol/L(MUREAV 326,165,1995)

Mutation in microorganisms; *S.typhimurium*; 11pph(ENVRAL 52, 225, 1990)

Cytogenetic analysis; human; lymphocyte; 2.5pph/24h(MUREAV 537, 117, 2003)

**Methanol**

Mutation in microorganisms; mouse; lymphocyte; 7900mg/L(ENMUDM 7(Suppl 3),10,1985)

**2-Propanol**

TDLo(ori,rat): 8mg/kg(female 6-15 D preg)(RTOPDW 23,183,1996)

TCLo(ihl,rat): 3500ppm/7h(female 1-19 D preg)(FCTOD7 26,247,1988)

**Carcinogenicity:****2-butanone**

Not available

**Ethanol**

TDLo(ori,mouse): 320mg/kg/50W-I(CALEDQ 13,345,1981)

**Methanol**

Not available

**2-Propanol**

Not available

**Reproductive toxicity:****2-butanone**

TCLo(ihl,rat): 2900mg/m<sup>3</sup>(female 6-10 D preg); Specific Developmental Abnormalities - craniofacial(VCVGK\* -, 418, 1994)

**Ethanol**

TDLo(ori,woman): 250mg/kg(37 W preg); Effects on Embryo or Fetus - other effects to embryo(AJOGAH 145,251,1983)

TDLo(ori,rat): 22.5mg/kg(female 11-20 D preg); Specific Developmental Abnormalities - Central Nervous Systems(NETEEC 24, 719, 2002)

**Methanol**

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

TCLo(ihl,rat): 10000ppm/7h(7-15 D preg)(FAATDF 5,727,1985)

TDLo(ori,rat): 5200µL/kg(10 D preg)(REPTED 11,503,1997)

2-Propanol

TDLo(ori,rat): 8mg/kg(female 6-15 D preg)(RTOPDW 23,183,1996)

TCLo(ihl,rat): 3500ppm/7h(female 1-19 D preg)(FCTOD7 26,247,1988)

### STOST-single exposure:

2-butanone

The influence of the central nervous system, rat/mouse(EHC 143, 1992; PATTY 4th, 1994; IRIS 2003)

The influence of kidney, oral, rat(DFGOT vol 12,1999; IRIS 2003; ATSDR 1992)

The respiratory tract irritation, human (ACGIH 7th, 2001; DFGOT vol 12,1999; PATTY 4th, 1994; ATSDR 1992)

Ethanol

Human ihl, 5000ppm(9,4mg/L), respiratory tract irritation and confusion(ACGIH 2001)

Methanol

The restraint of central nervous system and damage of the visual organ, human, oral or ihl(EHC 196,1997; ACGIH, 7th,2001; DFGOT vol.16, 2001),

The respiratory tract irritation, rat,(EHC 196,1997; PATTY 4th,1994),

Anesthesia, rat , mouse and rhesus monkey(EHC 196,1997;PATTY 4th,1994)

2-Propanol

Not available

### STOST-repeated exposure:

2-butanone

The sensory paralysis of hand and arm, human(EHC 143, 1992; DFGOT vol 12, 1999; IRIS 2003)

The damage of central nervous system, human(DFGOT vol 12, 1999; IRIS 2003)

Ethanol

Not available

Methanol

The restraint of central nervous system and damage of the visual organ, human, oral or ihl(EHC 196,1997; ACGIH, 7th,2001; DFGOT vol.16, 2001),

The respiratory tract irritation, rat,(EHC 196,1997; PATTY 4th,1994),

Anesthesia, rat , mouse and rhesus monkey(EHC 196,1997;PATTY 4th,1994)

2-Propanol

Not available

### Aspiration hazard:

2-butanone

Not available

Ethanol

Not available

Methanol

Not available

2-Propanol

Not available

## 12 Ecological information

### Ecotoxicity<sup>1)</sup>:

2-butanone

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

mosquito fish(96h-LC50(mg/L)):5600

daphnids(48h-LC50(g/L)):>1000

Ethanol

daphnids(48h-LC50(g/L)):5463.9(ECETOC TR91 2003)

Methanol

Not available

2-Propanol

guppies(7days-LC50(mg/L)):7060

fathead minnow(1h-LC50(mg/L)):11830

#### **Persistence and degradability:**

2-butanone

Not available

Ethanol

This material is biodegradable.

Methanol

This material is biodegradable.

2-Propanol

This material is biodegradable.

#### **Bioaccumulative potential:**

2-butanone

Not available

Ethanol

Not available

Methanol

Not available

2-Propanol

Not available

#### **Mobility in soil:**

2-butanone

Not available

Ethanol

Not available

Methanol

Not available

2-Propanol

Not available

### **13 Disposal considerations**

Scrap materials may be disposed by licensed contractor or burned in an approved incinerator.

Do not dump into sewer, on the ground or into any body of water.

Follow national and local regulations.

### **14 Transport information**

Follow all regulations in your country.

UN Number	:1210
UN Proper Shipping Name	:Printing ink, flammable
Transport hazard class	:Class 3(Flammable liquid)

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



---

Packing Group	: II
Environmental hazards	: No

## 15 Regulatory information

Follow all regulations in your country.

Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

## 16 References

- 1) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan
- 2) International Chemical Safety Cards

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.