# SAFETY DATA SHEET

# **1 IDENTIFICATION**

Product name Name of company Address Tel Fax Recommended use of the chemical and restrictions on use

:JP-G27 :Hitachi Industrial Equipment Systems Co., Ltd :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan :+81-294-36-8682 :+81-294-36-8975

:Printing Ink for industrial Marking

# **2 HAZARDS IDENTIFICATION**

Physico-chemical endpoints Acute toxicity - oral Acute toxicity - dermal Acute toxicity - inhalation(air) Acute toxicity - inhalation(vapors) Acute toxicity - inhalation(dust, mist)	: Flammable liquid Category 2 : Category 5 : Not available : Not identified : Not identified : Not identified
Skin corrosion/irritation	: Category 2 : Category 2
Eye damage/irritation Sensitization - respiratory	: Not identified
Sensitization - skin	: Not identified
Germ cell mutagenicity Carcinogenicity	: Not identified : Not identified
Toxic to reproduction	: Category 1
Effects on or via lactation	: Not identified
Specific target organ systemic toxicity Aspiration toxicity	: (Single exposure) Category 1 Sensory system Category 1 Systemic toxicity Category 1 Central nervous system Category 2 Kidney :(Repeated exposure) Category 1 Sensory system Category 1 Central nervous system Category 1 Peripheral nervous system : Not identified
Hazardous to the aquatic environment -Acute hazard -Chronic hazard	: Category 3 : Category 3

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



# Signal word: Danger

#### Hazard statement and precautionary statement:

- Highly flammable liquid and vapor
- May be harmful if swallowed
- Causes skin irritation
- Causes serious eye irritation
- May damage fertility or the unborn child
- Causes damage to Sensory system, systemic toxicity or central nervous system-single exposure
- May cause damage to kidney-single exposure
- Causes damage to sensory system, central nervous system or peripheral nervous system through prolonged or repeated exposure
- Harmful to aquatic life
- Harmful to aquatic life with long lasting effects

# **Precautionary statements:**

• Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

# **Prevention:**

- Keep away from ignition sources such as heat/sparks/open flame- No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

#### **Response:**

- In case of fire, use dry chemical, CO<sub>2</sub>, water splay (fog) or form for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

# Storage:

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

# **Disposal:**

• Waste must be disposed of according to applicable regulations.

# 3 Composition/information on ingredients

Substance or mixture; mixture	9	
Composition:		
Chemical name	concentration (%)	CAS number
2-butanone	55-65	78-93-3
Methanol	10-20	67-56-1
ChromeⅢ-Complex Dye	5-10	TSCA Registered
Copper-Complex Dye	1-5	TSCA Registered

# 4 First-aid measures

#### Inhalation;

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the neatest medical facility for examination and treatment by a physician as soon as possible.

#### Skin contact;

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

#### Eye contact;

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible. and refer for medical attention.

#### Ingestion;

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medical attention.

# 5 Fire-fighting measures

# Suitable extinguishing media;

Use dry chemical, CO<sub>2</sub>, water splay (fog) or form.

#### Fire fighting procedures;

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Avoid spraying water directly into storage containers due to danger of boil over.

# Unusual fire/explosion hazard;

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

# Special protective equipment and precautions for fire fighters;

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

### 6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

# 7 Handling and storage

#### Handling;

Use only in the well-ventilated areas. Make available in the work area emergency shower and eyes wash. Avoid contact with skin or eyes.

#### Storage;

Close up the container and keep it in dark cool(0~20°C) place. Keep away from combustible materials and sources of ignition.

### 8 Exposure controls/personal protection

#### Exposure guidelines:

ACGIH TLV-TWA (ppm)	
2-butanone	:200
Methanol	:200(skin)
ChromeⅢ-Complex Dye	:None known
Copper-Complex Dye	:None known
ACGIH STEL(ppm)	
2-butanone	:300
Methanol	:250(skin)
ChromeIII-Complex Dye	:None known

#### 9 Physical and chemical properties

Copper-Complex Dye

Appearance	
Physical state	:Liquid
Color	:Green
Odor	:Solvent odor
Boiling point <sup>2)</sup>	:80°C(2-butanone)
Flash point	:-4.1°C(closed cup)
Upper/lower flammability or explosive limits <sup>2)</sup>	:Lower 1.7 vol%、Upper 11.4 vol%
Vapor pressure <sup>2)</sup>	:10.5kPa (20°C) (2-butanone)
Vapor density (Air=1) <sup>2)</sup>	:2.41 (2-butanone)
Relative density	:0.89(20°C)
Solubility (Water) <sup>2)</sup>	:29g/100mL (20°C) (2-butanone)
Partition coefficient: n-octanol/water <sup>2)</sup>	:0.29(2-butanone)
Auto-ignition temperature <sup>2)</sup>	:505°C(2-butanone)

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

:None known

Decomposition temperature

:No data

# **10 Stability and reactivity**

Stability: The product is stable. Conditions and materials to avoid: Not available Hazardous decomposition products: These products are carbon oxides

# **11 Toxicological information**

#### Acute toxicity:

2-butanone LD50(orl,rat): 2737mg/kg(TXAPA9 19, 699, 1971) LCLo(ihl,rat): 23500mg/m/8h(AIHAAP 20, 364, 1959) LD50(skin,rabbit): 6480mg/kg(SHELL\* MSDS-5390-4) TCLo(ihl,human): 1000mg/m<sup>\*</sup>(VCVGK<sup>\*</sup> -, 417, 1994) LDLo(orl,human): 714.3mg/kg(VCVGK\* -, 417, 1994) Methanol LD50(orl,rat): 5628mg/kg(GTPZAB 19(11),27,1975) LC50(ihl,rat): 64000ppm/4h(NPIRI\* 1,74,1974) TDLo(orl,man): 9450µL/kg(AJEMEN 16,538,1998) TCLo(ihl,human): 300ppm(NPIRI\* 1,74,1974) Chrome III - Complex Dye Oral >5000(Rat LD50(mg/kg)) Dermal >2000(Rat LD50(mg/kg)) Inhalation None known Copper-Complex Dye None known

# Skin corrosion/irritation:

2-butanone Skin; rabbit; 402mg/24h; Mild(TXAPA9 19, 276, 1971) Methanol Skin; rabbit; 20mg/24h; Moderate(85JCAE -,187,1986) ChromeIII-Complex Dye No (Rabbit test-OECD404 1981) Copper-Complex Dye None known

#### Serious eye damage/irritation:

2-butanone Eye; rabbit; 80mg(TXAPA9 19, 276, 1971) Methanol Eye; rabbit; 100mg/24h; Moderate(85JCAE -,187,1986) ChromeⅢ-Complex Dye No(Rabbit test-84/449/EEC B.5) Copper-Complex Dye None known

#### Respiratory or skin sensitization:

2-butanone Not available
Methanol Allergic dermatitis; human, skin(PATTY 4th,1994) No skin sensitization ;Magnusson-Kligman maximization test, guinea pig(EHC 196,1997: DFGOT vol. 16,2001)
ChromeIII-Complex Dye No(Giunea pig test-84/449/EC B.6)
Copper-Complex Dye None known

Germ cell mutagenicity:

2-butanone

Reverse mutation assay in S.typhimuriun and E.coli; Negative Sex chromosome loss and nondisjunction; S.cerevisiae; 33800ppm(MUREAV 149, 339, 1985) Methanol Mutation in microorganisms; mouse; lymphocyte; 7900mg/L(ENMUDM 7(Suppl 3),10,1985) Chrome III-Complex Dye None known Copper-Complex Dye

None known

#### Carcinogenicity:

2-butanone Not available Methanol Not available Chrome III - Complex Dye None known Copper-Complex Dye None known

# Reproductive toxicity:

2-butanone TCLo(ihl,rat): 2900mg/m<sup>3</sup>(female 6-10 D preg); Specific Developmental Abnormalities craniofacial(VCVGK\* -, 418, 1994)
Methanol TCLo(ihl,rat): 10000ppm/7h(7-15 D preg)(FAATDF 5,727,1985) TDLo(orl,rat): 5200µL/kg(10 D preg)(REPTED 11,503,1997)
Chrome III-Complex Dye None known
Copper-Complex Dye None known

# STOST-single exposure:

2-butanone

The influence of the central nervous system, rat/mouse(EHC 143, 1992; PATTY 4th, 1994; IRIS 2003) The influence of kidny, oral, rat(DFGOT vol 12,1999; IRIS 2003; ATSDR 1992) The respiratory tract irritation, human (ACGIH 7th, 2001; DFGOT vol 12,1999; PATTY 4th,

1994; ATSDR 1992)

# Methanol

The restraint of central nervous system and damage of the visual organ, human, oral or ihl(EHC 196,1997; ACGIH, 7th,2001; DFGOT vol.16, 2001), The respiratory tract irritation, rat,(EHC 196,1997; PATTY 4th,1994), Anesthesia, rat, mouse and rhesus monkey(EHC 196,1997;PATTY 4th,1994) Chrome III-Complex Dye None known

Copper-Complex Dye None known

# STOST-repeated exposure:

#### 2-butanone

The sensory paralysis of hand and arm, human(EHC 143, 1992; DFGOT vol 12, 1999; IRIS 2003) The damage of central nervous system, human(DFGOT vol 12, 1999; IRIS 2003)

Methanol

The restraint of central nervous system and damage of the visual organ, human,

oral or ihl(EHC 196,1997; ACGIH, 7th,2001; DFGOT vol.16, 2001),

The respiratory tract irritation, rat, (EHC 196,1997; PATTY 4th, 1994),

Anesthesia, rat, mouse and rhesus monkey(EHC 196,1997;PATTY 4th,1994)

Chrome III - Complex Dye None known Copper-Complex Dye

None known

#### Aspiration hazard:

2-butanone Not available Methanol Not available ChromeⅢ-Complex Dye None known Copper-Complex Dye None known

# **12 Ecological information**

# Ecotoxicity<sup>1)</sup>:

2-butanone mosquito fish(96h-LC50(mg/L)):5600 daphnids(48h-LC50(g/L)):>1000 Methanol Not available ChromeIII-Complex Dye None known Copper-Complex Dye None known

# Persistence and degradability:

2-butanone Not available Methanol

This material is biodegradable. ChromeⅢ-Complex Dye None known Copper-Complex Dye None known

#### **Bioaccumulative potential:**

2-butanone Not available Methanol Not available Chrome III - Complex Dye None known Copper-Complex Dye None known

### Mobility in soil:

2-butanone Not available Methanol Not available Chrome III - Complex Dye None known Copper-Complex Dye None known

# **13 Disposal considerations**

Scrap materials may be disposed by licensed contractor or burned in an approved incinerator. Do not dump into sewer, on the ground or into any body of water. Follow national and local regulations.

# **14 Transport information**

Follow all regulations in your country.

UN Number	:1210
UN Proper Shipping Name	:Printing ink, flammable
Transport hazard class	:Class 3(Flammable liquid)
Packing Group	: <b>П</b>
Environmental hazards	:No

#### 15 Regulatory information

Follow all regulations in your country. Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

# **16 References**

- 1) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan
- 2) International Chemical Safety Cards