

SAFETY DATA SHEET

1 IDENTIFICATION

Product name :TH-76
Name of company :Hitachi Industrial Equipment Systems Co., Ltd
Address :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan
Tel :+81-294-36-8682
Fax :+81-294-36-8975
Recommended use of the chemical
and restrictions on use :Printing Ink for industrial Marking

2 HAZARDS IDENTIFICATION

Physico-chemical endpoints : Flammable liquid Category 2
Acute toxicity - oral : Category 5
Acute toxicity - dermal : Not available
Acute toxicity - inhalation (air) : Not identified
Acute toxicity - inhalation (vapors) : Not available
Acute toxicity - inhalation (dust, mist) : Not identified
Skin corrosion/irritation : Category 2
Eye damage/irritation : Category 2
Sensitization - respiratory : Not identified
Sensitization - skin : Not identified
Germ cell mutagenicity : Category 1
Carcinogenicity : Not available
Toxic to reproduction : Category 1
Effects on or via lactation : Not identified
Specific target organ systemic toxicity : (Single exposure)
Category 1 Sensory system
Category 1 Systemic toxicity
Category 1 Central nervous system
Category 2 Kidney
Category 3 Respiratory tract irritation
:(Repeated exposure)
Category 1 Liver
Category 1 Sensory system
Category 1 Central nervous system
Category 1 Peripheral nervous system
Category 2 Nervous system
Aspiration toxicity : Category 2
Hazardous to the aquatic environment
-Acute hazard : Not available
-Chronic hazard : Not available

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

GHS label elements

Hazard symbols:

**Signal word:** Danger**Hazard statement and precautionary statement:**

- Highly flammable liquid and vapor
- May be harmful if swallowed
- Causes skin irritation
- Causes serious eye irritation
- May cause genetic defects
- May damage fertility or the unborn child
- Causes damage to sensory system, systemic toxicity or central nervous system-single exposure
- May cause damage to kidney-single exposure
- May cause damage to airway irritant-single exposure
- Causes damage to liver, sensory system, central nervous system or peripheral nervous system through prolonged or repeated exposure.
- May cause damage to nervous system through prolonged or repeated exposure
- May be harmful if swallowed and enters airways

Precautionary statements:

- Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

Prevention:

- Keep away from ignition sources such as heat/sparks/open flame– No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

Response:

- In case of fire, use dry chemical, CO₂, water splay (fog) or foam for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Storage:

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

Disposal:

- Waste must be disposed of according to applicable regulations.

3 Composition/information on ingredients

Substance or mixture; mixture

Composition:

Chemical name	concentration (%)	CAS number
2-butanone	60-100	78-93-3
Methanol	10-30	67-56-1
Ethanol	3-7	64-17-5

4 First-aid measures

Inhalation;

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

Skin contact;

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

Eye contact;

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible. and refer for medical attention.

Ingestion;

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medical attention.

5 Fire-fighting measures

Suitable extinguishing media;

Use dry chemical, CO₂, water splay (fog) or form.

Fire fighting procedures;

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

Unusual fire/explosion hazard;

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

flashpoint.

Special protective equipment and precautions for fire fighters;

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

7 Handling and storage

Handling;

Use only in the well-ventilated areas.

Make available in the work area emergency shower and eyes wash.

Avoid contact with skin or eyes.

Storage;

Close up the container and keep it in dark cool(0~20°C) place.

Keep away from combustible materials and sources of ignition.

8 Exposure controls/personal protection

Exposure guidelines:

ACGIH TLV-TWA (ppm)

2-butanone	:200
Methanol	:200(skin)
Ethanol	:1000

ACGIH STEL(ppm)

2-butanone	:300
Methanol	:250(skin)
Ethanol	:No data

9 Physical and chemical properties

Appearance	
Physical state	:Liquid
Color	:Clear
Odor	:Solvent odor
Boiling point ²⁾	:78 to 80°C
Flash point	:-2.0°C (closed cup)
Upper/lower flammability or explosive limits ²⁾	:Lower 1.7 vol%, Upper 37 vol%
Vapor pressure ²⁾	:10.9kPa (20°C)
Vapor density (Air=1) ²⁾	:None known
Relative density	:0.80(20°C)
Solubility (Water) ²⁾	:None known
Partition coefficient: n-octanol/water ²⁾	:None known
Auto-ignition temperature ²⁾	:422 to 516°C
Decomposition temperature	:No data

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

10 Stability and reactivity

Stability: The product is stable.

Conditions and materials to avoid: Not available

Hazardous decomposition products: These products are carbon oxides

11 Toxicological information

Acute toxicity:

2-butanone

LD50(oral,rat): 2737mg/kg(TXAPA9 19, 699, 1971)

LCLo(ihl,rat): 23500mg/m³/8h(AIHAAP 20, 364, 1959)

LD50(skin,rabbit): 6480mg/kg(SHELL* MSDS-5390-4)

TCLo(ihl,human): 1000mg/m³(VCVGK* -, 417, 1994)

LDLo(oral,human): 714.3mg/kg(VCVGK* -, 417, 1994)

Methanol

LD50(oral,rat): 5628mg/kg(GTPZAB 19(11),27,1975)

LC50(ihl,rat): 64000ppm/4h(NPIRI* 1,74,1974)

TDLo(oral,man): 9450µL/kg(AJEMEN 16,538,1998)

TCLo(ihl,human): 300ppm(NPIRI* 1,74,1974)

Ethanol

TDLo(oral,man): 700mg/kg(NTOTDY 8,77,1986)

LD50(oral,rat): 9000mg/kg(VCVGK* -, 93, 1984)

LC50(ihl,rat): 20000ppm/10h(NPIRI* 1,44,1974)

TCLo(ihl,human): 2500mg/m³/20M(VCVGK* -, 93,1984)

Skin corrosion/irritation:

2-butanone

Skin; rabbit; 402mg/24h; Mild(TXAPA9 19, 276, 1971)

Methanol

Skin; rabbit; 20mg/24h; Moderate(85JCAE -,187,1986)

Ethanol

Skin; rabbit; 20mg/24h; Moderate(85JCAE -, 189, 1986)

Serious eye damage/irritation:

2-butanone

Eye; rabbit; 80mg(TXAPA9 19, 276, 1971)

Methanol

Eye; rabbit; 100mg/24h; Moderate(85JCAE -,187,1986)

Ethanol

rabbit; 100mg/4S; Moderate(FCTOD7 20,573,1982)

Respiratory or skin sensitization:

2-butanone

Not available

Methanol

Allergic dermatitis; human, skin(PATTY 4th,1994)

No skin sensitization ;Magnusson-Kligman maximization test, guinea pig(EHC 196,1997: DFGOT vol. 16,2001)

Ethanol

Not available

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Germ cell mutagenicity:

2-butanone

Reverse mutation assay in *S.typhimuriun* and *E.coli*; NegativeSex chromosome loss and nondisjunction; *S.cerevisiae*; 33800ppm(MUREAV 149, 339, 1985)

Methanol

Mutation in microorganisms; mouse; lymphocyte; 7900mg/L(ENMUDM 7(Suppl 3),10,1985)

Ethanol

DNA damage; *S.cerevisiae*; 850mmol/L(MUREAV 326,165,1995)Mutation in microorganisms; *S.typhimurium*; 11pph(ENVRAL 52, 225, 1990)

Cytogenetic analysis; human; lymphocyte; 2.5pph/24h(MUREAV 537, 117, 2003)

Carcinogenicity:

2-butanone

Not available

Methanol

Not available

Ethanol

TDLo(ori,mouse): 320mg/kg/50W-I(CALEDQ 13,345,1981)

Reproductive toxicity:

2-butanone

TCLo(ihl, rat): 2900mg/m³(female 6-10 D preg); Specific Developmental Abnormalities - craniofacial(VCVGK* -, 418, 1994)

Methanol

TCLo(ihl, rat): 10000ppm/7h(7-15 D preg)(FAATDF 5,727,1985)

TDLo(ori, rat): 5200µL/kg(10 D preg)(REPTED 11,503,1997)

Ethanol

TDLo(ori, woman): 250mg/kg(37 W preg); Effects on Embryo or Fetus - other effects to embryo(AJOGAH 145,251,1983)

TDLo(ori, rat): 22.5mg/kg(female 11-20 D preg); Specific Developmental Abnormalities - Central Nervous Systems(NETEEC 24, 719, 2002)

STOST-single exposure:

2-butanone

The influence of the central nervous system, rat/mouse(EHC 143, 1992; PATTY 4th, 1994; IRIS 2003)

The influence of kidney, oral, rat(DFGOT vol 12,1999; IRIS 2003; ATSDR 1992)

The respiratory tract irritation, human (ACGIH 7th, 2001; DFGOT vol 12,1999; PATTY 4th, 1994; ATSDR 1992)

Methanol

The restraint of central nervous system and damage of the visual organ, human, oral or ihl(EHC 196,1997; ACGIH, 7th,2001; DFGOT vol.16, 2001),

The respiratory tract irritation, rat,(EHC 196,1997; PATTY 4th,1994),

Anesthesia, rat , mouse and rhesus monkey(EHC 196,1997;PATTY 4th,1994)

Ethanol

Human ihl, 5000ppm(9,4mg/L), respiratory tract irritation and confusion(ACGIH 2001)

STOST-repeated exposure:

2-butanone

The sensory paralysis of hand and arm, human(EHC 143, 1992; DFGOT vol 12, 1999; IRIS 2003)

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The damage of central nervous system, human(DFGOT vol 12, 1999; IRIS 2003)

Methanol

The restraint of central nervous system and damage of the visual organ, human, oral or ihl(EHC 196,1997; ACGIH, 7th,2001; DFGOT vol.16, 2001),

The respiratory tract irritation, rat,(EHC 196,1997; PATTY 4th,1994),

Anesthesia, rat , mouse and rhesus monkey(EHC 196,1997;PATTY 4th,1994)

Ethanol

Not available

Aspiration hazard:

2-butanone

Not available

Methanol

Not available

Ethanol

Not available

12 Ecological information

Ecotoxicity¹⁾:

2-butanone

mosquito fish(96h-LC50(mg/L)):5600

daphnids(48h-LC50(g/L)):>1000

Methanol

Not available

Ethanol

daphnids(48h-LC50(g/L)):5463.9(ECETOC TR91 2003)

Persistence and degradability:

2-butanone

Not available

Methanol

This material is biodegradable.

Ethanol

This material is biodegradable.

Bioaccumulative potential:

2-butanone

Not available

Methanol

Not available

Ethanol

Not available

Mobility in soil:

2-butanone

Not available

Methanol

Not available

Ethanol

Not available

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

13 Disposal considerations

Scrap materials may be disposed by licensed contractor or burned in an approved incinerator.
Do not dump into sewer, on the ground or into any body of water.
Follow national and local regulations.

14 Transport information

Follow all regulations in your country.

UN Number	:1210
UN Proper Shipping Name	:Printing ink, flammable
Transport hazard class	:Class 3(Flammable liquid)
Packing Group	:II
Environmental hazards	:No

15 Regulatory information

Follow all regulations in your country.

Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

16 References

- 1) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan
- 2) International Chemical Safety Cards

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.